

# AZKEN

## AZ07800

### Key Features:

- IR LED: 36 PCs
- IR Range: 30M
- CS Lens: 2.8-12mm
- Water resistance: IP66
- Vandal Proof: IK 10
- Size: 131x 93(H)mm
- Weight:0.8kg



### Specifications:

|                                |   |
|--------------------------------|---|
| <b>MODEL</b>                   | <b>AZ07800</b>  |
| <b>Image Sensor</b>            | <b>1/3" CMOS, HDIS 960 H, with IR-Cut</b>                       |
| <b>Horizontal Resolution</b>   | <b>800 TVL</b>  |
| <b>Pixels</b>                  | <b>976 (H) X 582(V)</b>   |
| <b>TV System</b>               | <b>PAL/NTSC</b>   |
| <b>IR Series Distance</b>      | <b>30M</b>  |
| <b>IR LED</b>                  | <b>36 PCs</b>   |
| <b>Lens</b>                    | <b>2.8-12mm Manual Zoom Lens</b>                                |
| <b>Sync System</b>             | <b>Internal</b>   |
| <b>Usable Illumination</b>     | <b>0.01Lux/F2.0</b>   |
| <b>S/N Ratio</b>               | <b>≥ 48dB (AGC OFF)</b>   |
| <b>Gamma Correction</b>        | <b>0.45</b>   |
| <b>Video Out</b>               | <b>Composite Signal (1.0Vp-p, 75Ω)</b>                          |
| <b>Scanning System</b>         | <b>PAL:625 Lines, 50 Field/Sec;NTSC:525 Lines, 60 Field/Sec</b> |
| <b>Electronic Shutter Time</b> | <b>Auto: PAL 1/50-1/100, 000Sec;NTSC 1/60-1/100, 000Sec</b>     |
| <b>Operation Temperature</b>   | <b>-10°C ~ +50°C RH95% Max</b>                                  |
| <b>Storage Temperature</b>     | <b>-20°C ~ +80°C RH95% Max</b>                                  |
| <b>White Balance</b>           | <b>Auto</b>   |
| <b>Power Source</b>            | <b>DC12V 400mA</b>  |
| <b>Dimension</b>               | <b>131 x 93(H)mm</b>  |
| <b>Weight</b>                  | <b>800g</b>   |

\*Looks, features and specifications are subject to change