



AZ-32CH1

FEATURES

- 32 CH H.264 compression format
- Mobile monitoring, support iPhone, Blackberry, Android, windows Mobile and Symbian.
- IE, Web client, and CMS monitoring, send Email when alarm.
- Free DDNS bound, simple to operate, support UPNP(Universal Plug and Play), no need to do complicated IP forwarding.
- Digital zoom function on both preview and playback mode.
- Support privacy masking, and user right management.
- support NTSC/PAL video system
- 32 CH video inputs, 1CH monitor output, 2CH spot monitor output, 1CH VGA output(1280*1024)
- 8CH audio inputs, 1CH audio output
- High quality image, brightness, contrast, sharpness and color adjustable for each channel
- Support video sequence display
- Display modes: PIP, FULL, QUAD, 8 SPLIT, 9/16 /32SPLIT
- Recording modes: always recording, manual recording, schedule recording, sensor recording and motion recording
- Detailed event log support
- Searching modes: time/date searching, event searching, urgent searching
- Support fast forward and rewind: x2, x4, x8, support jog-shuttle operation
- Back up modes: network backup, USB back up
- Support RS-485 PTZ control(speed dome camera), and preset position operation
- Support USB mouse and infrared remote controller operation
- Support 4 SATA port HDD
- 16 CH alarm inputs,2CH alarm output
- Multiplex operation: live/recording/playback/network can be operated at the same time
- Telemetry network control: live view, playback, recording and so on
- Frame rate in the preview mode:960fps@CIF(NTSC), 800fps@CIF(PAL)
- Frame rate in the playback mode:960fps@CIF(NTSC), 800fps@CIF(PAL)

Model	AZ-32CH1	
Video Compression format	H.264	
Language	Multi-languages	
Video System	NTSC	PAL
Video Input	32CH , NTSC/PAL, 1.0VP-P/75Ω, BNC*32	
Video Outputs	1CH monitor output, 2CH vice-monitor. VGA output	
Video Resolution	704* 480	704* 576
Display Modes	Full screen, multiple screens, Sequence display, exchangeable channel display, picture-in-picture	
Audio Input	-8Db22kΩ,RCA connector×8	
Audio Input	-8Db3kΩ,RCA connector×1	
Alarm Input	16CH	
Alarm Output	2CH	
Recording Modes	Manual, Continue, alarm, motion detection	
Operating System	Embedded Linux	
Operating Method	USB mouse, remote control, control panel	
Multiplex Operation	live & record & playback & backup & network	
Frame and Resolution	CIF:NTSC 960fps/360*240	CIF:PAL 800fps/360*288
Watchdog (LED indicator)	Power, channel, backup, network	
Event Modes	Alarm trigger, motion detection trigger	
High Playback Speed	2, 4, 6 multiplier , single frame playback	
Playback Searching	Date & time search, event list search, Emergent search	
Playback Modes	Support 32CH playback simultaneously	
Network Protocols	TCP/IP, DHCP&PPPOE & DDNS	
Network Port	10M/100M Ethernet port	
Mobile monitoring	Windows mobile, Symbian, Iphone	
Confidential Function	User and administrator Password Protection	
PTZ Control	RS485, preset positions operation	
HDD Port	Support 4 SATA hard disk	
HDD Occupation Space	All32 channels record at high quality mode8GB/H	
Backup System	USB,CD-RW, network backup, AVI format backup	
Power Supply	DC : 12V/5A	
Power consumption	20W	
Dimensions	430 (L) * 360 (W) * 90 (H) mm	
Weight	6.0KG(No HDD)	
Environment	Operating Temperature: +5°~ +50° Storage Temperature: -20°~ +70° Humidity: 30 ~95%	